

# INDIRECT FIRED HEATERS



FVO-200



FVP-200

MODEL	FVO-200 Oil	FVN-200 Natural Gas	FVP-200 Propane
<b>Heat Capacity</b>	200,000 btuh	200,000 btuh	200,000 btuh
<b>Fuel Tank Capacity</b>	23 US gallons	External N/A	External N/A
<b>Operating Time/ Fuel Consumption</b>	15 hours 1.50 Gal/hr	190 CFH	9.25 lbs/hr
<b>L x W x H</b>	51.5" x 27" x 43.5"	53.5" x 27" x 39.5"	53.5" x 27" x 39.5"
<b>Heat Exchanger</b>	18 gauge 304 Stainless Steel	18 gauge 304 Stainless Steel	18 gauge 304 Stainless Steel
<b>Fan Motor</b>	1/2 HP@1,725 RPM 1,500 CFM	1/2 HP@1,725 RPM 1,500 CFM	1/2 HP@ 1,725 RPM 1,500 CFM
<b>Ignition</b>	Direct Spark Ignition	Direct Spark Ignition	Direct Spark Ignition
<b>Nozzle Size/ Gas Pressure</b>	1.25 x 60B @ 145PSI	3.5" W.C.	3.5" W.C.
<b>Air Outlet</b>	One 12" diameter	One 12" diameter	One 12" diameter
<b>Wheels</b>	Two 12" pneumatic/ Two 6" swivel Lockable casters	Two 12" pneumatic/ Two 6" swivel Lockable casters	Two 12" pneumatic/ Two 6" swivel Lockable casters
<b>Power Requirement</b>	115V/15 Amp	115V/15 Amp	115V/15 Amp
<b>Approvals</b>	cETLus	cETLus	cETLus
<b>Weight</b>	330 lbs	280 lbs	280 lbs

## OPTIONS

For all FV-Series



12" x 12' Flexible Ducting  
12" x 25' Flexible Ducting



Remote Thermostat Control  
with 25 ft Cord

