

BTF 150

SPECIFICATIONS

Fuel	Vapor Propane
Input - Maximum	150,000 BTU/hour
Input - Minimum	50,000 BTU/hour
Manifold Pressure	2-1/4 to 20 PSIG
Hose Length	20 ft. is standard
Regulator With POL	Adjustable to 20 PSI max.
Approval	Underwriters' Laboratories of Canada Listed
Weight	27 lbs.
Length	30 in.
Width	11.25 in.
Height	14 in.
Air Outlet	8 in. Diameter
Fuel Consumption	2.3 to 6.9 lbs. per hour
Ignition	Manual
Optional Fan	N/A



Direct Fired Construction Heater

FEATURES

- Engineered for simple operation and minimal servicing
- Light and highly portable
- Stackable for easy transportation and storage
- Designed to withstand rough and tough applications
- Designed to operate without a fan or electricity
- F-150 - Adjustable Heat From 50,000 to 150,000 BTU/hr
- Temporary heat for use during construction and maintenance

ACCESSORIES



2001-S2
2 cylinder manifold



2001-S3
3 cylinder manifold

Aerotech Herman Nelson Intl. Inc.
100 Eagle Drive
Winnipeg, MB, CAN
R2R 1V5

1 (800) 486-4328
1 (204) 633-1999 (24hr)

sales@hermannelson.com
www.hermannelson.com