AEROTECH HERMAN NELSON BTIDF 500 OIL/DIESEL

FEATURES

- Standard Lifting Bail Included
- Industrial Grade Beckett Burner (Oil/Diesel Version)
- Can be configured with 2 x 12" or 1 x 16" Outlet front Cap
- 42 ^{U.S.} Gallon Environmental Spill Containment Fuel Tank Included (Oil/Diesel Version)
- Optional Heat Recovery System Available to Minimize Service Calls (Oil/Diesel Version)
- 2.3" Static Pressure Increased duct lengths & pressurization for larger structures (Model IDF500HS Only)
- GeniSys Controller with Diagnostic Reader (Oil/Diesel Version)

IDF500 OIL SPECIFICATIONS Capacity 500,000 BTU/hour **Electrical Requirements** 115V/20 AMP **Air Flow** 3,100 CFM .5″ Static Fan Motor 1Hp, 1800 RPM **Burner Motor** 1/4HP@3450 RPM **Shipping Dimensions** 70"L x 35"H x 50"W **Shipping Weight** 520 lbs. CSA Approval Fuel No 1 fuel oil or kerosene 2.5 GPH @ 165 PSI Nozzle Tank Capacity 35 Imperial gallons 42 ^{U.S.} Gallons

IDF500 OIL HS SPECIFICATIONS

> Capacity 500,000 BTU/hour Electrical Requirements 115V/25 AMP Air Flow 3,250 CFM Static 2.3" Motor 1.5 Hp Shipping Dimensions 83"L x 37"H x 52"W Shipping Weight 580 lbs. Approval CSA Fuel Oil

Made in Canada

AEROTECH



Full Environmental Spill Containment around poly tank

Aerotech Herman Nelson Intl. Inc. 100 Eagle Drive Winnipeg, MB, CAN R2R 1V5

> 1 (800) 486-4328 1 (204) 633-1999 _(24hr)

sales@hermannelson.com www.**hermannelson**.com Pg. 21