

The Blaze 200 DG Turbo

The Blaze 200 DG Turbo (LP/NG/OIL-FIRED)

Introducing the most efficient and high performance heater in its class. 85% Efficient with Recirculating Capabilities to minimize your fuel costs!

FEATURES:

- Whisper Quiet Operation
- Discharge Temperature up to 250 °F
- Recirculating Capabilities
- Small footprint with Forklift Pockets & Lifting Bar with 16" tires for easy handling
- Stainless Steel Heat Exchanger
- Powder Coat Finish
- Easy LP/NG Switchover
- Beckett Burner Options for both Oil and Gas
- Redundant Fail Safe Control System
- Oil Pressure Gauge
- Thermostat Operation
- Genysis Beckett Controller

Specifications

- 190,000 BTU/H
- 2,750 CFM Highest in its Class
- Ductability: 150ft., Max 50ft on return
- 5" of static Pressure
- 85% Efficient
- 120V/15A/60HZ Full Load Amps: 9A
- Dry Weight: 250lbs
- Overall Dimensions: 48.5" x 30.6" x 41"
- 20 US Gallon Fuel Tank
- 15-17 Hours of Run Time
- CSA/UL Approved



Aerotech Herman Nelson Intl. Inc.
100 Eagle Drive
Winnipeg, MB, CAN
R2R 1V5

1 (800) 486-4328
1 (204) 633-1999 (24hr)

sales@hermannelson.com
www.hermannelson.com